



(19)

(11) Publication number:

05021378 A

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **03202931**

(51) Int. Cl.: **H01L 21/28** H01L 21/205 H01L 21/225
H01L 21/28 H01L 21/82 H01L 21/3205
H01L 27/04 H01L 21/331 H01L 29/73
H01L 21/336 H01L 29/784

(22) Application date: **13.08.91**(30) Priority: **31.08.90 JP 02228124**(43) Date of application
publication:
29.01.93(84) Designated contracting
states:
JP(71) Applicant: **HITACHI LTD**

(72) Inventor: **KOBAYASHI TAKASHI**
SHINPEI
HIRAIWA ATSUSHI
KOBAYASHI NOBUYOSHI
MITSUO
NANBA HASHIMOTO KOJI

(74) Representative:

**(54) MANUFACTURE OF
SEMICONDUCTOR DEVICE**

(57) Abstract:

PURPOSE: To provide a method of manufacturing a silicon film including boron which ensures excellent step-portion covering characteristic and is just suitable for

manufacturing process under a low temperature condition.

CONSTITUTION: An amorphous Si film is deposited by the pressure-reduced CVD method under a low temperature of 200 or higher and 400°C or lower using any one of disilane (Si₂H₆) or trisilane (Si₃H₆) and diborane (B₂H₆). Thereby, a Si film including boron which ensures excellent step-portion covering characteristic can be formed. Using the obtained Si film as a diffusion source, extremely shallow junction may be formed.

COPYRIGHT: (C)1993, JPO&Japio



